

PRODUCT CARD



PRODUCT CODE: OR-AE-13601

EAN CODE: 5908254802096

Cable Connector, Straight, 3x4mm², 450V/25A

This MINI cable connector is small in size and simple in shape. High ingress protection level IP68 guarantees resistance against difficult weather conditions and an additional sealing with an O-ring secures the product against chemical and mechanical damage. The material used for connector's production is resistant to UV rays and is suitable for outdoor use. This robust and firm construction as well as our innovative sealing solution make the product suitable for underground installation. Its contacts are made of brass with additional nickel layer to secure them against oxidation. Cable gland is equipped with a thick gasket to tightly seal all cables inside.



Wire cross-section:

4mm²



Number of wires:

3



Current:

25A



UV radiation resistance:



Case flammability standard

UL94:

V1



Degree of protection (IP):

68

General information

Connector type: MINI straight

Wire cross-section: 4 mm²

Number of wires: 3

Cable gauge: 6-12 mm mm

Power supply: 450V

Current: 25 A

Contacts material: nickel-plated brass

Flame-resistant casing: yes

UV radiation resistance: yes

Case flammability standard UL94: V1

Dimensions - length (mm): 24 mm

Degree of protection (IP): 68

Type of connection: screw clamp

Underground installation: yes

Material housing: PA6