

PRODUCT CARD



PRODUCT CODE: OR-AE-13615

EAN CODE: 5908254821042

4-way cable connector (X-type), IP68, 3x4mm², 450V/25A

This small-sized X-type cable connector is suitable for cables with a maximum cross-section of 4mm². High degree of tightness IP68 guarantees resistance against external factors, and the innovative O-Ring seal does not expose the seal to damaging external, chemical and mechanical conditions. The material used for the production of the connector is resistant to UV rays and is suitable for outdoor use. Its rigid, compact form and innovative sealing enable installation in the ground. The contacts are made of brass, additionally protected against oxidation with a layer of nickel. The cable gland is equipped with a thick gasket that tightly seals all inserted wires.



Wire cross-section:

4mm²



Number of wires:

3



Current:

25A



UV radiation resistance:



Case flammability standard

UL94:

V1



Degree of protection (IP):

68

General information

Connector type: Type X 4-way

Wire cross-section: 4 mm²

Number of wires: 3

Cable gauge: 6-12 mm

Power supply: 450V

Current: 25 A

Contacts material: nickel-plated brass

Flame-resistant casing: yes

UV radiation resistance: yes

Case flammability standard UL94: V1

Dimensions - length (mm): 100 mm

Degree of protection (IP): 68

Type of connection: screw clamp

Underground installation: yes

Material housing: PA6

Diameter: 24 mm