

## Flush-mounted motion sensor 360°, IP65, 1200W

Marka: Orno | Symbol: OR-CR-267 | Ean: 5908254812842

**ORNO**


### PRODUCT DESCRIPTION

This motion sensor is suitable for flush-mounting in suspended ceilings. It can control lighting or other electric appliances. Additional features of the product: mechanical adjustment of the sensors position, potentiometers to adjust activation time and light intensity. This sensor is LED-compatible. High ingress protection level (IP65) of the sensor makes it suitable for outdoor installation.

## TECHNICAL DATA

### General information:

|  |   |
|--|---|
| Max. load:                                   | 1200 W                                    |
| Max. load of the LED light source:           | 300 W                                     |
| Degree of protection (IP):                   | 65  |
| Relay output:                                | Yes                                       |
| Nominal voltage:                             | 230V~, 50Hz                               |
| Presence detector:                           | Yes                                       |
| Colour:                                      | white                                     |
| Installation:                                | flush mounting                            |
| Dimensions of the sensor - width (mm):       | 87,3 mm                                   |
| Dimensions of the sensor - height (mm):      | 76 mm                                     |
| Dimensions of the sensor - depth (mm):       | 76 mm                                     |
| Working temperature:                         | -20~+40                                   |
| Other features:                              | 3 sensors                                 |
| Detection angle:                             | 360°                                      |
| Dimensions of the mounting hole:             | 61,5 mm                                   |
| Type of sensor:                              | infrared                                  |
| Detection range:                             | Ø6 m                                      |
| Adjustable daylight sensor (LUX):            | Yes                                       |
| Daylight sensor adjustment range (LUX):      | <3–2000lux                                |
| Adjustable time setting (TIME):              | Yes                                       |
| Lighting time adjustment range (TIME):       | min.: 10 sek. ± 3 sek., max.: 15min.±2min |
| Adjustment of motion detection range (SENS): | No  |



