

PRODUCT CARD



PRODUCT CODE: OR-PSU-1643 EAN CODE: 5908254803840

DIN rail power adaptor 12V DC 2A, 24W, width: 2 units

Highly efficient and reliable DIN rail power adaptor of 24W max. load and 12V DC output voltage, which can be adjusted. It has been developed for DIN rail installation and can be used in vast number of applications, e.g. industrial applications, low voltage installations, such as CCTV or alarm systems. This power adaptor includes: overload protection, anti-surge protection and overvoltage protection. An integrated diode indicates activation of the device.





24W



Output voltage:

12V DCV



Input voltage:

100-230V 50-60Hz



No. of modules (width):

2



Installation:

a DIN rail



General information

| Over voltage category: | III |
|---------------------------------|------------------|
| Rated power: | 24 W |
| Output voltage: | 12V DC V |
| Input voltage: | 100-230V 50-60Hz |
| Max. short time current rating: | 2,1A |
| Output current: | 2 A |
| Standby power consumption: | 0.3 W |
| No. of modules (width): | 2 |
| Short-circuit protection: | yes |
| Current protection: | yes |
| Installation: | a DIN rail |
| Voltage protection: | yes |
| Degree of protection (IP): | 20 |
| Dimensions - depth: | 35 mm |
| Dimensions - height: | 58 mm |
| Voltage adjustment: | yes |